

# Please measure your rim before you order your MOVIT Braking systems!

Dear customer,  
please do not hesitate to contact us for any question. Thank you.

## Front braking systems:

304 4-Kolben = 355 mm

322 4-Kolben = 375 mm

342 4-Kolben = 398 mm

342 6-Kolben = 397 mm

370 4-Kolben = 420,5 mm

370 6-Kolben-BILLET = 424 mm

380 4-Kolben = 428 mm

380 6-Kolben-BILLET = 437 mm

396 6-Kolben-BILLET = 448 mm

420 6-Kolben-BILLET = 472 mm

436 6-Kolben-BILLET = 494 mm

460 6-Kolben-BILLET = 520 mm

## Rear braking systems:

299 4-Kolben = 346 mm

322 4-Kolben = 370 mm

342 4-Kolben = 395 mm

362 4-Kolben = 415 mm

380 4-Kolben = 433 mm

400 4-Kolben = 453 mm

## Combination of MOVIT® Front and Rear braking systems:

bis 342 mm VA = 322 mm an HA

bis 380 mm VA = 342 mm an HA

ab 396 mm VA = 380 mm an HA

## 1. Measure rim diameter at the narrowest point



## 2. Distance to friction ring

Measured at the inner side of the crossing, at the nearest position to the original brake pad. (min.: 65-70 mm)



VA = Front brake system, HA = Rear brake system

**Hotline** +49 (0) 7223-28165-0 / [mail@movitbrakes.com](mailto:mail@movitbrakes.com)